# PRODUCT INFORMATION



Automotive Chemicals - Technical Sprays - Protection

Version: TS/018

## Valvoline™ Electro Protect

High quality electro preservative to prevent starting problems caused by moisture.

#### **Applications**

**Switches** 

**Batteries** 

Multiple sockets

Cables

Electric tools

Plugs

Electric systems which should to be protected

against moisture

Spark plugs

Printed circuit board switches

Distributor caps

Fuses

Current distributors

#### **Product characteristics**

Water/ Moisture repellent Good penetrating properties Excellent corrosion prevention properties Excellent adhesion properties 360° valve

#### **Directions for use:**

Before use, carefully read the directions on the packaging.

Valvoline™ Electro Protect should be at room temperature before use. The processing temperature should be between 5 to 30°C. Shake before use.

Switch off electrical installations before treatment

Parts to be treated must be clean, dry and free of grease before using the product.

Apply Valvoline™ Electro Protect in several thin layers for the best result.

# PRODUCT INFORMATION



### Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **www.valvolineeurope.com** 

#### **Typical properties**

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline™ Electro Protect	
Contents	500 ml
Basis	Mineral Oil
VOC-content	Approx. 85%
	w/w
Colour	Transparent
Scent	Characteristic
Relative density at 20°C	0,802 g/ml
Yield	1,9 g/sec
Refractive Index at 20°C	1,444
Vapour pressure at	3 to 4 bar
20°C	
pH-value	Neutral

This information only applies to products manufactured in the following location(s): Europe

### **Health & Safety**

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet http://sds.valvoline.com

#### Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

#### Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces -

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

<sup>™</sup> Trademark of Valvoline, registered in various countries © 2018