

KITO





Neutral eye protection

Description and composition:

Polycarbonate frame with soft PVC nose piece for excellent protection and comfort

Polycarbonate lenses with TPR appliqués for effective impact absorption.

FT marking: resistance to low-energy and high-velocity impacts at extreme temperatures.



Modern design with wrap-around lens for better impact protection. Excellent upper and side protection Double-injected temples for greater comfort.

UV 400 filter lenses: 100% protection against harmful ultra-violet light.

Colour:





Weight: 24 g



Double-injected temples



Double-injected temples for greater comfort



Also in brown solar and clear anti-fogging: FT marking

Colour	Ref.	Product	Lens Marking	Frame Marking
CLEAR	912.313	Clear polycarbonate anti-scratch and anti-fogging spectacles cert.	2C-1,2 M 1 FTKN CE	
GREEN	911.880	Clear polycarbonate anti-scratch spectacles	2C-1,2 M 1 FT CE	M EN166 FT CE
	911.883	Clear polycarbonate anti-fogging spectacles	2C-1,2 M 1 FT CE	
	912.691	Clear polycarbonate anti-reflective spectacles	2C-1,2 M 1 FT CE	
	911.886	Solar polycarbonate anti-fogging spectacles	5-2,5 M 1 FT CE	
BLUE	911.881	Clear polycarbonate anti-scratch spectacles	2C-1,2 M 1 FT CE	
	911.884	Clear polycarbonate anti-fogging spectacles	2C-1,2 M 1 FT CE	
	912.692	Clear polycarbonate anti-reflective spectacles	2C-1,2 M 1 FT CE	
	911.887	Solar polycarbonate anti-fogging spectacles	5-2,5 M 1 FT CE	

Neutral eye protection

Standard and certification	EN-166 EN-170 EN-172			
Applications	Protection against low-energy and high-velocity impacts at extreme temperatures.			
	Industries: mining, quarries, aeronautics, renewable energy, refineries, automotive industry, sports, transport, maintenance, electronics. And in general any outdoor or indoor work with risk of impact.			
Conservation Storage - Expiry	In order to maintain the spectacles in good condition, keep them in a clean, dry place in their appropriate case.			
Directions Use	Polycarbonate cleaning: use warm water and a neutral soap. Do not use abrasives or solvents. Rinse in water and dry with a soft cloth. Medop anti-fogging cleaning spray is also recommended. We advise regular inspection of the protectors, and their replacement if they have deteriorated in any way.			
Presentation	Individual polybag with bar code 12 units per box 25 units per carton			
Bar code	911.880 GTIN-13: 8423173877712 GTIN-14: 68423173877714 911.883 GTIN-13: 8423173877743 GTIN-14: 68423173877745 912.691 GTIN-13: 8423173886783 GTIN-14: 68423173886785 911.886 GTIN-13: 8423173877774 GTIN-14: 68423173877776 911.881 GTIN-13: 8423173878269 GTIN-14: 18423173877726 911.884 GTIN-13: 8423173877750 GTIN-14: 68423173877752 912.692 GTIN-13: 8423173886790 GTIN-14: 68423173886792 911.887 GTIN-13: 8423173877781 GTIN-14: 68423173877783			

