

ik

BY EXPERTS
FOR EXPERTS

HC



www.iksprayers.com

EN

Industrial sprayer especially manufactured with highly resistant materials for use with animal and vegetable oils, hydrocarbon-based solvents, lubricants and petroleum products.

- Automotive: brake cleaning, tar removal from vehicle bodies and tools, cleaning of car interiors and de-waxing fluids.
- Industry: machinery and motor cleaning and lubricant application.
- Construction: wood treatments and waterproofing.



IK HC 1.5



CODE: 8.17.74

All parts of the sprayer including the washers are resistant to oils and most hydrocarbons and solvents • 2.5 bar safety valve with depressurization option • Large filling opening • Ergonomic design • Strong translucent tank with level indicator • Protective sleeve for valve chamber • Easily taken apart for maintenance • Tool free • Adjustable conical nozzle.

TECHNICAL SPECIFICATIONS

TOTAL CAPACITY	1.50 l. – 0.39 U.S. Gallons.
USEFUL CAPACITY	1 l. – 0.26 U.S. Gallons.
LITRES/MIN. 3 BAR	0.50 l/min. - 1 pint/min.
GROSS WEIGHT	0.60 Kg – 1.32 lbs.
NET WEIGHT	0.46 Kg – 1.02 lbs.

CHEMICAL PRODUCTS TABLE

The following table shows several examples of the most frequently used aggressive substances and the model recommended for each use. Follow the specified maximum percentages.

Important: Not suitable for spraying acid agents or strong alkalines.

Given the wide variety of products on the market, Goizper does not warrant the universal validity of its products. Always use caution when working and follow the instructions of the chemical manufacturer.

		IK MULTI	IK ALKALINES	IK HC	IK METAL/INOX
ACIDS	ACETIC ACID (MAX 20%)	L	✓	×	×
	HYDROCHLORIC ACID (MAX 30%)	✓	L	×	×
	HYDROFLUORIC ACID (MAX 20%)	✓	×	×	×
	PHOSPHORIC ACID	✓	L	×	×
	NITRIC ACID (MAX 20%)	✓	L	×	×
	SULPHURIC ACID (MAX 30%)	✓	L	×	×
	OTHER ACIDS	✓	L	×	×
ALCOHOLS	BUTANOL	L	✓	L	L
	ETHANOL	L	✓	L	L
	METHANOL	L	✓	L	L
	OTHER ALCOHOLS	L	✓	L	L
ALIPHATIC HYDROCARBONS	DECANE	L	×	✓	✓
	HEPTANE	L	×	✓	✓
	HEXANE	L	×	✓	✓
	LIMONENE	L	×	✓	✓
	PENTANE	L	×	✓	✓
AROMATIC HYDROCARBONS	NAPHTHALENE	L	×	✓	✓
	TOLUENE (MAX 40%)	L	×	✓	✓
	XYLENE	L	×	✓	✓
OILS AND PETROLEUM PRODUCTS	MINERAL-VEGETAL OIL	L	×	✓	✓
	DIESEL	L	×	✓	✓
	GASOLINE	L	×	✓	✓
	KEROSENE	L	×	✓	✓
	WHITE SPIRIT	L	×	✓	✓
ALKALINES AND KETONES	ACETONE	×	✓	×	×
	AMMONIA	L	✓	×	×
	SODIUM HYDROXIDE (CAUSTIC SODA)	×	✓	×	×
	POTASSIUM HYDROXIDE	×	✓	×	×
	SODIUM HYPOCHLORITE	L	L	×	×

Not suitable for acids

✓ OPTIMUM L LIMITED ✗ NOT SUITABLE



Workshops



Construction



Automotive cleaning



Industry

Goizper Group
Growing through cooperation

Antigua, 4
20577 Antzuola
Gipuzkoa - Spain

Tel.: + 34 943 786 000
spraying@goizper.com
www.iksprayers.com

T06500444

Goizper Spain | Goizper Portugal | Goizper France | Goizper UK | Goizper Central Europe | Goizper Russia | Goizper North America | Goizper Central America | Goizper Brazil | Goizper Middle East | Goizper West Asia | Goizper Asia-Pacific | Goizper West Africa | Goizper East Africa