

TECHNICAL DATA

ADVANTAGES AND BENEFITS

- > Multilayer Strong Backing
- > Easy Tear
- > Multipurpose

TYPICAL APPLICATIONS

- > Repairs
- > Fixing
- > Reinforcing
- > Many more...

CONSTRUCTION

Overall Grade: General Purpose
 Backing: Synthetic cloth extruded & laminated
 Adhesive: Synthetic Rubber/ Resins

COLOR(S)

- Silver
 Black
 White
 Red

STANDARD SIZE

Width(s): 48mm / 2"
 Length(s): 50m / 55yd

Contact your BDT sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD VALUES	UNITS	TOLERANCE
Thickness	180 / 7	my / mil	(+/- 10%)
Adhesion to Stainless Steel 180°	≥ 15	N/2,5cm	-
Tensile Strength	30	N/cm	(+/- 5%)
Service Temperature Range	from -5 to +60	° C	-
	from 23 to 140	F	-

The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and performed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.