



PRODUCT INFORMATION

a product of NITEO™ Products

PYROIL™ POWER STEERING FLUID

DESCRIPTION:

Pyroil Power Steering Fluid was specially formulated to meet the OEM specifications: GM 9985010, Ford ESW-M2C128 C and D, and Chrysler MS-5931E. Not recommended for use in Honda power steering units. Blended from highly-refined base oils fortified with special additives to help prevent wear corrosion and foaming. **Pyroil Power Steering Fluid** helps maintain superior efficiency and performance of power steering units. Prevents leakage and squealing under severe conditions. Protects against pump breakdown caused by wear, oxidation and foaming. Effective in high and low temperatures. Performs in subzero temperatures to insure cold weather performance. Will not clog or foam. Helps prevent corrosion, wear and oxidation. Use year-round.



Check the level of the power steering fluid at least once a year. Although the fluid level may be checked hot or cold, it should be checked while hot if possible. If the power steering fluid is low, check the owner’s manual for proper fluid specifications before adding fluid. Do not overfill.

Part Number	Description	Unit UPC
PYPSF12P	Pyroil Power Steering Fluid 12/12 oz.	0 28882 10006 9
PYPSF32	Pyroil Power Steering Fluid 12/32 oz.	0 28882 10008 3

BENEFITS:

- Meets OEM Specifications
- Keeps Seals and O-Rings Pliable
- Helps Maintain Efficiency & Performance
- Helps Prevent Leakage
- Reduces Squealing Under Severe Conditions
- Prevents Corrosion, Oxidation & Wear
- Will Not Clog or Foam
- For Year-Round Use

FOR MORE INFORMATION, VISIT WWW.NITEOPRODUCTS.COM OR CALL 844-696-4836

This information applies only to products manufactured in the following location(s): USA, Canada

Effective Date: 12/1/2014	Expiration Date: 12/1/2019	Replaces: 6/1/2008	Author's Initials: DET	Pages: 2
------------------------------	-------------------------------	-----------------------	---------------------------	-------------



PRODUCT INFORMATION

a product of NITEO™ Products

TECHNICAL DATA:

Appearance	Liquid
Color	Amber
Viscosity @ 100 °C, cSt	7-8 cSt
Viscosity @ 40 °C, cSt	35-40 cSt
Density @60 °F	0.870 – 0.890
Flash Point COC	347 °F minimum
Pour Point, °C (max)	-40 °C

FOR MORE INFORMATION, VISIT WWW.NITEOPRODUCTS.COM OR CALL 844-696-4836

This information applies only to products manufactured in the following location(s): USA, Canada

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Pages:
12/1/2014	12/1/2019	6/1/2008	DET	2

All information herein is believed to be true and correct, but is not to be taken as a representation or warranty, express or implied, including any warranty with respect to merchantability or fitness for any particular purpose. ™Trademark, Niteo, registered in various countries. ©2015, Niteo.