

## Technical Data Sheet

# Interflon Fin Super Dry Lube

## Universal dry film lubricant with MicPol® technology

Multipurpose penetrating dry long-lasting lubricant for a variety of indoor and outdoor applications. Repels water, dust, sand and other contaminants. Removes and prevents rust.

Cleans, lubricates and protects (CLP). Goes on wet, cleanses, displaces moisture, breaks down deposits and penetrates even into the most inaccessible areas. Loosens seized, rusted and frozen parts and prevents the formation of rust and other corrosives. Holds up to high pressures, resists water wash-off and will not attract dirt, dust and other abrasives.

### Applications

Where parts are exposed to contamination or moisture, they need to be coated to prevent rust and corrosion; providing protection where conventional lubricants fail. Excellent choice for the lubrication of bikes, fishing equipment, guns, locks, doors, skateboards/skates, watercrafts, boats, electrical components (dielectric), cars/trucks, blades, wire ropes, zippers, hinges and many other applications.

### Advantages

- ◊ Reduction of wear
- ◊ Contains no propellant, 100% product
- ◊ Small, practical packaging for easy handling
- ◊ Clean and dry lubricant, does not drip
- ◊ Longer lasting
- ◊ Replaces many other products
- ◊ Water resistant
- ◊ Frees sticking parts
- ◊ Cleans and protects against corrosion
- ◊ Dirt does not stick to the dry film
- ◊ Stable lubricating film with MicPol®
- ◊ No stick slip

### Instructions for use

Shake or stir before use. Parts should be cleaned first with a solvent or alkaline cleaning agent. Spray Interflon Fin Super Dry Lube onto parts and allow to penetrate. Wipe off the excess of lubricant with a clean cloth.

Note: Do not use too much Interflon Fin Super Dry Lube. Applying a thin layer, with occasional re-lubrication, gives a better result than a thick layer.

### Safety regulations

See safety data sheet.

### Packaging

See our current article list

### Transport regulations

**Technical Data Sheet**

# Interflon Fin Super Dry Lube

**Universal dry film lubricant with MicPol® technology**
**Technical data**

Property	Value	Standard
Composition	Mixture of mineral and vegetable oils, additives and MicPol®.	
Colour	Yellow brown	
Odour	Oily	
Density @ 20°C	0.85 g/cm <sup>3</sup>	
Kinematic viscosity @ 40°C	21 cSt	ASTM D445
Pour point	-43°C (-45°F)	ASTM D97
Lowest application temperature	-43°C (-45°F)	
Highest application temperature*	170°C (338°F)	
Friction coefficient	0.02-0.06 (MicPol®)	
Dielectric strength	128 kV/cm	IEC 60156
Conductivity	> 2000 pS/m	ASTM D2624
Biodegradability	53%	ASTM D7373-07
Shelf life**	4 years	

\* High temperature limit is valid after evaporation of solvent.

\*\* Shelf life of the product when stored at room temperature in the original and unopened packaging.

*This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale. Interflon® /MicPol® is a registered trademark of Interflon BV.*

*Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information contained herein is subject to change without notice.*



For more information and demonstration:  
[holland@interflon.com](mailto:holland@interflon.com)

[www.interflon.com](http://www.interflon.com)

IF-FS-DL.01

28-10-2019 | 2/2