






# Technical Data Sheet


<p><b>General</b></p> <p>Article number: 53820x Description: Disposable Nitrile Gloves Grey</p>	
<p><b>Specification:</b> Specially developed Nitrile Gloves for use during the painting process. This powder, silicon and latex free gloves combines extra protection with extra comfort due to its high elasticity. Especially suitable for working with paints. With extra long sleeves (300 mm) and textured surface for better grip.</p> <p><b>Features and benefits:</b></p> <ul style="list-style-type: none"> <li>- Extra thick 8 mil (0.2 mm)</li> <li>- Extra long sleeves (300 mm)</li> <li>- Extra strong, flexible and higher tensile strength</li> <li>- Textured finger tips for better grip</li> <li>- Especially suitable for working with paints</li> </ul> <p><b>Remarks:</b></p> <ul style="list-style-type: none"> <li>- <b>Natural latex free</b> The gloves are natural latex-free. Absolutely safe to wear for people with a latex allergy.</li> <li>- <b>Silicone free</b> The gloves are silicon free. This prevents contamination of the pant.</li> <li>- <b>Powder free</b> The gloves are washed 3 times during production. This makes them 100% powder free to prevent paint contamination.</li> <li>- <b>Single use</b> The gloves are designed to be disposed after use. This prevents contamination and guarantees clean working.</li> </ul> <div style="text-align: center;">  </div> <p><b>Certificates:</b> Personal Protective Equipemt (PPE) : CAT III according to European regulation 2016/425/EU. PPE of complex design protects against risks that cause irreversible damage to health.</p> <p><b>CE</b>      Notified body number: 2777</p> <p><b>EN 1149-5</b>       Tested acc. to EN 1149-3, Method 2: Induction decay time. Anti-static</p>	

## EU Type Examination Test Results:

Tested in accordance with	Performance level	AQL	Inspection Levels
<b>EN ISO 374-5: 2016</b>  <b>VIRUS</b> Specified: Level 2 (AQL<1.5) acc. to producer	Level 3	< 0.65	G1
	Level 2	< 1.5	G1
	Level 1	< 4.0	S4

<b>Tested in accordance with</b> <b>EN ISO 374-1: 2016 Type B</b>  <b>JKOPT</b>	96% Sulphuric Acid (L) – Level 1 Degradation: 100% n-Heptane (K) – Level 3 Degradation: 37.3% 40% Sodium Hydroxide (K) – Level 6 Degradation: -12.2% 25% Ammonium Hydroxide (O) – Level 2 Degradation: -8.4% 30% Hydrogen Peroxide (P) – Level 3 Degradation: -6.6% 37% Formaldehyde (T) – Level 5 Degradation: 2.8%	
	Level 1: > 10 minutes Level 2: > 30 minutes Level 3: > 60 minutes	Level 4: > 120 minutes Level 5: > 240 minutes Level 6: > 480 minutes

Sizing Chart		
Measurement	Glove Size	Article number
8	Medium	Art. no. 538200
9	Large	Art. no. 538202
10	Extra Large	Art. no. 538204



**Single use only**

Made in Thailand

### Technical Specification:

Colour	Grey
Packing	Dispenser box of 50 pieces
Packaging Unit	Box of 10 dispenser boxes
Material	Nitrile
Thickness	8 mil.
Length	300 mm
Available sizes	538200 – Size M 538202 – Size L 538204 – Size XL

### Approved by:

#### SATRA Technology Europe Ltd

Bracetown Business Park  
 Clonee, D15 YN2P Ireland

### Related products of Colad

Article number: 5000 – Description: Respirator A1P2  
 Article number: 5200xx – Description: BodyGuard® Comfort Overall

**Disclaimer**

Technical Data Sheet & Material Safety Data Sheet; it is the responsibility of the user to read understands and apply the information of the TDS. The information about work and environmental safety is available on the material safety data sheet (MSDS) via [www.colad.co](http://www.colad.co). It is the responsibility of the user to read and apply the information.

Products are for professional use. Necessary protective equipment and clothing should be worn. The repairs should always be done in accordance with the OEM rules and specifications. All information is for the user's consideration, investigation and verification. The specific use applications and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of any of the products mentioned for the user's specific application.

**Created by:**

EMM International BV  
Bohemstraat 19, 8028 SB Zwolle, The Netherlands  
[www.emm.com](http://www.emm.com)



T +31(0)38 467 66 00  
[www.colad.co](http://www.colad.co)